











Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No	Name and description	Price in NOK
1000	<p>PLT Launching Unit without Air Cylinder or Cover Launching Unit without Air Cylinder or Cover.</p>	
1005	<p>PLT Launching Unit Launching Unit with Air Cylinder and Cover. Contents: 1 Art No 1306 Air Cylinder 1 Art No 1000 Launching Unit 1 Art No 1017 Cover for Air Cylinder</p>	
1006	<p>PLT Launching Unit US Launching Unit with Air Cylinder (certified for the US and Canadian market) and Cover. Contents: 1 Art No 1307 Air Cylinder 1 Art No 1000 Launching Unit 1 Art No 1017 Cover for Air Cylinder</p>	
1011	<p>Complete Accumulator Piston Complete piston for PLT Launching Unit.</p>	





Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No	Name and description	Price in NOK
1013	Firing Valve	
1017	Cover for Air Cylinder	
1021	Reduction Valve complete	
1031	Safety Valve	
1050	Complete Set of Packing and O-rings Packings and O-rings for the PLT Launching Unit	
1054	Hatch Lock w/ Loop 2 pcs	

Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No	Name and description	Price in NOK
1060	Trigger Handle Complete Trigger Handle for PLT Launching Unit.	
1303	Launching Tube Rescue 230 Launching Tube for Projectile Rescue 230 and the Art No 1005/1006.	
1306	Air Cylinder complete Air Cylinder w/ closing valve. 1,45 liter (50 fl oz). Working pressure 300bars/4350psi. Note! The new valve does not fit old covers (Art No 1017).	
1307	Air Cylinder US complete Air Cylinder w/ closing valve. 1,45 liter (50 fl oz), certified for the US and Canadian market. Working pressure 200bars/2900psi. Note! The new valve does not fit old covers (Art No 1017).	
1308	Adapter 200/300 bar (Yoke-DIN477) Adapter for filling of the air cylinder from Yoke 200 bars (2900psi) standard.	

Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No	Name and description	Price in NOK
1309	Closing Valve with Manometer Note! The new valve does not fit old covers (Art No 1017). Old valves can be provided on request.	
1310	Air Filling Hose w/ Connections Air filling hose with couplings and pressure releaser. Connection between compressor and Air Cylinder, or Air Cylinder to Air Cylinder (male-male and 5/8" threads according to DIN 477).	
1312	Air Filling Hose w/ Connections Air filling hose with couplings and pressure releaser. Connection between PLT Launching Unit and Air Cylinder. Connection between Quick Coupling for the PLT Mini and Air Cylinder (male-female and 5/8" threads according to DIN 477).	
1502	Pivot Support Used for a safer handling of the PLT. Should be used with the Pivot Tube (Art No 1503).	

Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No	Name and description	Price in NOK
--------	----------------------	--------------

1503 Tube for Pivot Support
Should be welded at a convenient location for operating the PLT. Has to withstand 500kg recoil.



2000 PLT Rescue 230 complete
Complies with IMO/SOLAS 74/83, Line Throwing Appliances.

Contents:

- 1 Art No 1005 PLT Launching Unit
- 1 Art No 1303 Launching Tube Rescue 230
- 4 Art No 2101 Projectile Rescue 230
- 1 Art No 2200 Loading Device Projectile Rescue 230
- 1 Art No 3303 Launching Tube 150
- 1 Art No 7004 Projectile PLT 150
- 1 Art No 6201 Linebox 5mm Floating Line
- 1 USB stick and User Manual



Typical shooting range with a dry and clean line of 3,2mm (Art No 2103): 230m
Breaking strength of the line: 2000N (204kg).




2000 SOLAS Upgrade
UPGRADE Upgrade your PLT Launching unit to comply with SOLAS LTA.
No expiry date.
The minimum launching distance is 230 meters.

Contents:





- 4 Art No 2101 Projectile Rescue 230
- 1 Art No 1303 Launching Tube Rescue 230







Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No	Name and description	Price in NOK
2001	PLT Rescue 230 US complete Certified for the US and Canadian market.	
2002	PLT R230 with Ball Projectiles PLT Rescue 230 and PLT 75 complete according to IMO/Solas 74/83, Line Throwing Appliances. Contents: 1 Art no 1005 PLT Launching Unit 1 Art no 1303 Launching Tube Rescue 230 4 Art no 2101 Projectile Rescue 230 1 Art no 2200 Loading Device Projectile Rescue 230 1 Art no 6201 Linebox 5mm Floating Line 1 Art no 6303 Launching Tube PLT 75 2 Art no 6101 Projectile Ball 1 USB stick and User Manual Typical shooting range with a dry and clean line of 3,2mm(Art No 2103): 230m Breaking strength of the line in Art No 2101 : 2000N (204kg). Breaking strength of the line in Art No 6201 : 4315N (440kg).	
2003	PLT Rescue 230 Basic Complies with IMO/SOLAS 74/83, Line Throwing Appliances. Contents: 1 Art No 1005 PLT Launching Unit 1 Art No 1303 Launching Tube Rescue 230 4 Art No 2101 Projectile Rescue 230 1 USB stick and User Manual Typical shooting range with a dry and clean line of 3,2mm (Art No 2103): 230m Breaking strength of the line: 2000N (204kg).	






Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No	Name and description	Price in NOK
2011	<p>PLT R 230 Complete Same as Art No 2000, but comes with Art No 5202 Linebox 3,2mm Nylon instead of Art No 6201 Linebox 5mm Floating Line.</p>	
2101	<p>Projectile Rescue 230 Projectile for PLT Rescue 230. Made from ABS plastic and aluminum. The line is stored inside the projectile. The Rescue projectile must never be launched without the end plug (Art No 2104). Typical shooting range with a dry and clean line of 3,2mm (Art No 2103): 230m Breaking strength of the line: 2000N (204kg).</p>	
2103	<p>Safety Line Projectile Rescue 230 3,2mm of Safety Line for Art No 2101. Comes on a spool of 250 meters. Breaking strength of the line: 2000N (204kg).</p>	
2104	<p>End Plug for Projectiles with Internal Line End plug for Projectile Rescue 230 (Art No 2101), Projectile Rescue 150 (Art No 3101), Projectile PLT/Mini-Rescue Buoy and Projectile PLT Mini 100 (Art No 4101). The projectiles must never be fired without the end plug.</p>	

Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No	Name and description	Price in NOK
2105	<p>Line 2mm Hollow Braided Dyneema Comes on a spool of 350 meters. Breaking strength of the line: 7800N (795kg).</p>	
2200	<p>Loading Device Projectile Rescue 230 Loading Device for Art No 2101, Projectile Rescue 230. Connect to a low-pressure source, 5-8 bars/75-110psi, and it will insert the safety line back into the projectile.</p>	
3000	<p>PLT Rescue 150 complete Contents: 1 Art no 1005 PLT Launching Unit 1 Art no 3303 Launching tube PLT 150 2 Art no 3101 Projectile Rescue 150 1 Art no 7004 Projectile PLT 150 1 Art no 6201 Linebox 5mm Floating Line 1 Art no 3200 Loading Device Projectile Rescue 150 1 USB stick and User Manual</p> <p>Typical shooting range with a dry and clean line of 3,2mm(Art No 2103): 140-150m Breaking strength of the line : 2000N (204kg).</p>	
3000 UPGRADE	<p>PLT Rescue 150 Upgrade Contents: 2 Art No 3101 Projectile Rescue 150 1 Art No 3303 Launching Tube 150</p> <p>Typical shooting range with a dry and clean line of 3,2mm(Art No 2103): 140-150m Breaking strength of the line : 2000N (204kg).</p>	

Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No	Name and description	Price in NOK
3001	PLT Rescue 150 US complete Certified for the US and Canadian market.	
3101	Projectile Rescue 150 Made from ABS plastic and aluminum. The line is stored inside the projectile. Typical shooting range with a dry and clean line of 3,2mm (Art No 2103): 150m Breaking strength of the line: 2000N (204kg).	
3200	Loading Device Projectile Rescue 150 Loading Device for Art No 3101, Projectile Rescue 150. Connect to a low-pressure source, 5-8 bars/75-110psi, and it will insert the safety line back into the projectile.	
3303	Launching Tube 150 Launching Tube for Projectile Rescue 150 and Projectile PLT 150.	
4000	PLT Mini complete Contents: 1 Art No 4020 PLT Mini Launching Unit 1 Art No 4006 CO2 Cartridge 4-pack 2 Art No 4101 Projectile PLT Mini 100 1 Art No 4102 Projectile PLT Mini-Rubber 1 Art No 4200 Loading Device Projectile PLT Mini 100 1 Art No 4202 Linebox 2mm Nylon Line	

Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No	Name and description	Price in NOK
--------	----------------------	--------------

1 USB stick and User Manual

Typical shooting range with a dry and clean line of 2mm (Art No 4110) and Projectile PLT Mini 100 Art No 4101: 100m.

Typical shooting range with a dry and clean line of 2mm (Art No 4110) and Projectile PLT Mini-Rubber Art No 4102 : 90m.

Breaking strength of the line: 1863N (190kg).

The PLT Mini is a light version shoulder launched PLT.

4000U PLT Mini complete without CO2

The PLT Mini is a light version shoulder launched PLT. This is the standard package, which is the same as Art No 4000, but excludes CO2 cartridges.



4006 CO2 Cartridge, 4-pack

Disposable 33-gram CO2 Cartridges. Comes in a 4-pack. Note that these can be shipped by air as dangerous goods.






4020 PLT Mini Launching Unit





The PLT Mini can be used either with CO2 Cartridges (Art No 4006) or compressed air.







Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No	Name and description	Price in NOK
4021	PLT Mini Launching Unit Black Same as Art No 4020, but in black version.	
4050	PLT Mini Line Retrieval Contents: 1 Art No 4020 PLT Mini Launching Unit 1 Art No 4006 CO2 Cartridge 4-pack 1 Art No 4114 Projectile PLT Mini-Line Pick-Up Grapple 1 Art No 4203 Linebox 2mm Dyneema Line 1 USB stick and User Manual	
	Typical shooting range with a dry and clean line of 2mm and 4114: 75m. Breaking strength of the line: 7800N (795kg).	
4060	PLT Mini Complete Rescue Pack Contents: 1 Art No 4020 PLT Mini Launching Unit 5 Art No 4006 CO2 Cartridge 4-pack 2 Art No 4101 Projectile PLT Mini 100 1 Art No 4102 Projectile PLT Mini-Rubber 1 Art No 4104 Lightstick (5-pack) 1 Art No 4200 Loading Device Projectile PLT Mini 100 2 Art No 4202 Linebox 2mm Nylon Line 1 Art No 4100 Storage Container PLT Mini 1 USB stick and User Manual	
	Typical shooting range with a dry and clean line of 2mm (Art No 4110) and Projectile PLT Mini 100 Art No 4101: 100m. Typical shooting range with a dry and clean line of 2mm (Art No 4110) and Projectile PLT Mini-Rubber Art No 4102 : 90m. Breaking strength of the line: 1863N (190kg). The PLT Mini is a light version shoulder launched PLT.	




Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No	Name and description	Price in NOK
4100	<p>Storage Container PLT Mini</p> <p>Water proof container in heavy duty plastic. Easy storage and easy handling. Air and water tight. It even floats in the water. Internal dim. 580x440x220 mm, External dim. 650x510x242mm. 56liter and 8,5kg. Color: Orange.</p>	
4101	<p>Projectile PLT Mini 100</p> <p>Projectile PLT Mini 100 is made from ABS plastic and has a aluminum inner tube. Filled with an internal line of 110m (120yd). The projectile floats in the water.</p> <p>Typical shooting range with a dry and clean line of 2mm (Art No 4110): 100m. Breaking strength of the line: 1863N (190kg).</p>	
4102	<p>Projectile PLT Mini-Rubber</p> <p>Soft projectile made from Polyurethane. Used for general line transfer and training. A lightstick can easily be attached for visibility at night. Must be used with external line. Other options of line on request.</p> <p>Typical shooting range with a dry and clean line of 2mm (Art No 4110): 90m. Breaking strength of the line: 1863N (190kg).</p>	
4103	<p>Projectile PLT Mini-Sharp Grapple</p> <p>Grapple with sharp ends for pick-up. Made from POM and Stainless Steel. The projectile does not float. Must be used with external line. Other options of line on request.</p> <p>Typical shooting range with a dry and clean line of 2mm (Art No 4110): 75m. Breaking strength of the line: 1863N (190kg).</p>	




Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No	Name and description	Price in NOK
4104	<p>Lightstick for Projectile PLT Mini-Rubber 5 pcs. Lighsticks for Art No 4102. Provides visibility during night time. Green color with 6 hours burning time. Comes in a 5-pack.</p>	
4105	<p>Projectile PLT/Mini-Rescue Buoy Projectile that contains an automatic inflatable life buoy. Will inflate within 2 sec. after entering the water. Can be used with PLT and PLT Mini. The inflator has an expiry date. Uses 33gram CO2 cartridge. Buoyancy 155 N. Must be used with external line. Other options of line on request.</p> <p>Typical shooting range with a dry and clean line of 2mm (Art No 4110) with the PLT Mini: 80m. Breaking strength of the line: 1863N (190kg). Typical shooting range with a dry and clean line of 3,2mm (Art No 2103) with the PLT: 115m. Breaking strength of the line: 2000N (204kg).</p>	
4105U	<p>Projectile PLT/Mini-Rescue Buoy without CO2 The same as Art No 4105, but without CO2.</p>	
4106	<p>Projectile PLT Mini-Rubber Tip Rubber tipped plastic projectile that floats. Used for general line transfer or as a training projectile for PLT Mini. Must be used with external line. Other options of line on request.</p> <p>Typical shooting range with a dry and clean line of 2mm (Art No 4110) with the PLT Mini: 95m. Breaking strength of the line: 1863N (190kg).</p>	





Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No	Name and description	Price in NOK
4110	<p>Safety Line PLT Mini Projectiles Safety line for all PLT Mini Projectiles, 2mm and 120m.</p> <p>Breaking strength of the line: 1863N (190kg).</p>	
4111	<p>Packings and O-rings PLT Mini Launching Unit Packings and O-rings for PLT Mini.</p>	
4114	<p>Projectile PLT Mini-Line Pick-Up Grapple Closed grapple for line pick-up. The closed ends secures the line within the barbs. Made from Stainless Steel and plastic.</p> <p>Must be used with external line. Other options of line on request.</p> <p>Typical shooting range with a dry and clean line of 2mm (Art No 4110) with the PLT Mini: 75m. Breaking strength of the line: 1863N (190kg).</p>	
4115	<p>Projectile-Entering Grapple 3 Titanium grapple with 3 tines that are barbed from center to the tip. Holds a calculated tension of 300kg. For entering constructions. Fits lines up to 9mm for direct climbing after launching. Can be used with PLT and PLT Mini Launching Unit.</p> <p>Typical shooting range with a dry and clean double line of 3,2mm (Art No 2103) by PLT: 64m Typical shooting range with a dry and clean double line of 3,2mm (Art No 2103) by PLT Mini: 29m Using 9mm Technora fibers single line and PLT: 37m Using 9mm Technora fibers single line and PLT Mini: 16m</p>	




Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No	Name and description	Price in NOK
4116	<p>Projectile-Entering Grapple 4</p> <p>Titanium grapple with 3 tines that are barbed from center to the tip. Carries test certificate with max obtained tension of 600kg at the center before bending. For entering constructions. Fits lines up to 9mm for direct climbing after launching. Can be used with PLT and PLT Mini Launching Unit.</p> <p>Typical shooting range with a dry and clean double line of 3,2mm (Art No 2103) by PLT: 64m Typical shooting range with a dry and clean double line of 3,2mm (Art No 2103) by PLT Mini: 29m Using 9mm Technora fibers single line and PLT: 37m Using 9mm Technora fibers single line and PLT Mini: 16m</p>	
4200	<p>Loading Device Projectile PLT Mini 100</p> <p>Loading Device for reloading the 2mm (Art No 4110) line into Art No 4101 and Art No 4202. Connect to a low-pressure source, 5-8 bars/75-110psi, and it will insert the safety line back into the projectile or linebox.</p>	
4202	<p>Linebox 2mm Nylon Line</p> <p>Linebox containing safety line (min 90m of Art No 4110). Reloads using Loading Device Projectile PLT Mini 100, Art No 4200.</p> <p>Breaking strength of the line: 1863N (190kg).</p>	




Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No	Name and description	Price in NOK
4203	Linebox 2mm Dyneema Line Linebox containing 2mm Dyneema Safety Line (100m). Breaking strength of the line: 7800N (795kg).	
4207	Quick Coupling Quick Coupling for reloading PLT Mini with compressed air. Fits any standard 5/8" diving cylinder. Reduces the air pressure to correct working pressure. With our Air Cylinder Art No 1306/1307, you will get 22 (with 300bars) / 14 (with 200bars) shots. Art No 1312 can be used in order to connect with an air cylinder.	
4303	Launching Tube PLT Mini Launching Tube for PLT Mini.	
5000	PLT 150 complete Line thrower for general line transfer. Contents: 1 Art No 1005 PLT Launching Unit 1 Art No 3303 Launching Tube 150 2 Art No 7004 Projectile PLT 150 1 Art No 5202 Linebox 3,2mm Nylon. Other options of line on request. 1 USB stick and User Manual. Typical shooting range with a dry and clean line with 3,2mm (Art No 2103): 140m Breaking strength of the line: 2000N (204kg).	





Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No	Name and description	Price in NOK
5000 UPGRADE	<p>PLT 150 Upgrade All parts are re-useable.</p> <p>Contents: 2 Art No 7004 Projectile PLT 150 1 Art No 3303 Launching Tube 150 1 Art No 5202 Linebox 3,2mm Nylon</p> <p>Typical shooting range with a dry and clean line with 3,2mm : 140m. Breaking strength of the line: 2000N (204kg).</p>	
5001	<p>PLT 150 US complete Certified for the US and Canadian market.</p>	
5050	<p>Line Retrieval Kit Heavy Duty Used for picking up various types of lines from water.</p> <p>Contents: 1 Art No 1005 PLT Launching Unit 1 Art No 3303 Launching Tube 150 1 Art No 7002 Projectile PLT-Line Pick-Up Grapple 1 Art No 6203 Linebox 5mm HMPE. Other options of line on request 1 USB stick and User Manual.</p> <p>Typical shooting range with a dry and clean line with 5mm: 85m Breaking strength of the line: 19613N (2000kg).</p>	





Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No	Name and description	Price in NOK
5050 UPGRADE	<p>PLT Line Retrieval Upgrade All parts are re-useable.</p> <p>Contents: 1 Art No 7002 Projectile PLT-Line Pick-Up Grapple 1 Art No 3303 Launching Tube 150 1 Art No 6203 Linebox 5mm HMPE</p> <p>Typical shooting range with a dry and clean line with 5mm: 85m. Breaking strength of the line: 19613N (2000kg).</p>	
5202	<p>Linebox 3,2mm Nylon Linebox containing 150m (164 yd) of 3,2mm (0.13 in) of line (Art No 2103). Used for maximum range for Projectile PLT 150, Art No 7004. Breaking strength of the line: 2000N (204kg).</p>	
6000	<p>PLT 75 complete Line thrower for general line transfer.</p> <p>Contents: 1 Art No 1005 PLT Launching Unit 1 Art No 6303 Launching Tube PLT 75 2 Art No 6101 Projectile Ball 1 Art No 6201 Linebox 5mm Floating Line. Other options of line on request 1 USB stick and User Manual.</p> <p>Typical shooting range with a dry and clean line with 5mm (Art No 6109): 90m Breaking strength of the line: 3236N (330kg).</p>	






Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No	Name and description	Price in NOK
6000 UPGRADE	<p>PLT 75 Upgrade All parts are re-useable.</p> <p>Contents: 2 Art No 6101 Projectile Ball 1 Art No 6303 Launching Tube PLT 75 1 Art No 6201 Linebox 5mm Floating Line</p> <p>Typical shooting range with a dry and clean line with 5mm: 75m. Breaking strength of the line: 3236N (330kg).</p>	
6001	<p>PLT 75 US complete Certified for the US and Canadian market.</p>	
6101	<p>Projectile Ball Ball projectile for PLT 75. Filled with air and coolant preventing bouncing and freezing. Typical shooting range with a dry and clean line of 5mm (Art No 6109): 90m. Breaking strength of the line: 4315N (440kg).</p>	
6102	<p>Line 5mm Braided Nylon Line, 120m 5mm (131yd 0.2in) braided nylon. Breaking strength of the line: 5884N (600kg).</p>	

Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No	Name and description	Price in NOK
6103	<p>Line 5mm Braided Dyneema Line, 100/120m 5mm (109/131yd 0.2in) braided Dyneema (HMPE). Floats and has very little elongation under stress. Breaking strength of the line: 19613N (2000kg).</p>	
6109	<p>Line 5mm Polypropylene Line, 120m 5mm (131yd 0.2in) Polypropylene. Floats and has a very bright yellow color. Breaking strength of the line: 3236N (330kg).</p>	
6200	<p>Loading Device complete for 5mm Line Loading Device for 5mm line. Connect to a low-pressure source, 5-8 bars/75-110psi, it will refill the safety line back into the linebox.</p>	
6201	<p>Linebox 5mm Floating Line Linebox containing Line 5mm Polypropylene, Art No 6109. 120m (131yd). Floats and has a very bright yellow color. Breaking strength of the line: 3236N (330kg).</p>	

Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No	Name and description	Price in NOK
6202	<p>Linebox 5mm Nylon Line Linebox containing line 5mm Braided Nylon, Art No 6102. 120m (131yd). Breaking strength of the line: 5884N (600kg).</p>	
6203	<p>Linebox 5mm HMPE Linebox containing Line 5mm Braided Dyneema, Art No 6103. 100/120m. Floats and has very little elongation under stress. Breaking strength of the line: 19613N (2000kg).</p>	
6303	<p>Launching Tube PLT 75 Launching Tube for Art No 6101 Projectile Ball. Typical shooting range with a dry and clean line of 5mm (Art No 6109): 90m.</p>	
6304	<p>Launching Tube PLT 75 Extended Version Launching Tube for Art No 6101 Projectile Ball. Typical shooting range with a dry and clean line of 5mm (Art No 6109): 110m.</p>	
7002	<p>Projectile PLT-Line Pick-Up Grapple Closed grapple for line pick-up. The closed ends secures the line within the barbes. Made from Stainless Steel and plastic. Must be used with external line. Other options of line on request. Typical shooting range with a dry and clean line of 5mm</p>	

Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No	Name and description	Price in NOK
---------------	-----------------------------	---------------------

(Art No 6102): 85m.
Breaking strength of the line: 5884N (600kg).

7003	Projectile PLT 150-Lightstick Floating plastic projectile with lightstick holder. 2 lightsticks included. Must be used with external line. Other options of line on request.
------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------



Typical shooting range with a dry and clean line of:
5mm (Art No 6102): 90m
3,2mm (Art No 5202): 130m.

7004	Projectile PLT 150 Rubber tipped plastic projectile that floats. Used for general line transfer or as a training projectile. Must be used with external line. Other options of line on request.
------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------








Typical shooting range with a dry and clean line of:
5mm (Art No 6109): 115m
3,2mm (Art No 2103): 140m.




7005	Lightstick Holder For Art No 4106, Art No 7003 and Art No 7004. If you want to launch during night and use our lightstick (Art No 7020 and Art No 7021).
------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------




Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No	Name and description	Price in NOK
7020	<p>Lightstick Orange, 5 min/10 pcs. 5 minutes burning time with full effect. Comes as a 10-pack. Used with Art No 7003 or Art No 7005.</p>	
7021	<p>Lightstick Yellow, 30 min/10 pcs. 30 minutes burning time with full effect. Comes as a 10-pack. Used with Art No 7003 or Art No 7005.</p>	
7023	<p>Spare Rubber Tip with nut For Art No 4106 and 7004.</p>	
7032	<p>Repacking Set Life Buoy w/ CO2 Repacking set for life buoy Art No 7035 and Art No 4105. Includes inflator, strips and a 33gram CO2 cartridge. The inflator has an expiry date.</p>	
7034	<p>Repacking Set Life Buoy without CO2 Repacking set for life buoy Art No 7035 and Art No 4105. Includes inflator and strips. The inflator has an expiry date.</p>	





Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No	Name and description	Price in NOK
7035	<p>Rescue Egg</p> <p>Rescue Egg containing an automatically inflatable life buoy. No line attached. Ideal for MOB when ship is moving. The cover acts as a sea anchor. The inflator has an expiry date. Uses 33gram CO2 cartridge.</p>	
7038	<p>Quick Link Ladder Connector</p> <p>Minimum order amount 2. Using the optional Ladder Connector the spacing remains the same when joining two ladders (order 2 for the Single Rung Ladder or order 3 for the Double Rung Ladder). CE-EN 362.</p>	
7039	<p>Ladder Single Rung 10m</p> <p>10m, lightweight, noiseless, non conducting, contains no metal parts and presents no radar signal. Built for heavy duty military use in marine environment! One end of the ladder has a single attachment point for fast and easy deployment. The other end has a two separate attachment points. You can use this side to put 2 ladders together (with the optional Ladder Connectors) or you can use this side to connect it to two separate anchor points to rig it slightly more stable. Single Rung 200mm width. Rung spacing: 30cm. Using the optional Ladder Connector (Art No 7038) the spacing remains the same when joining two ladders (order 2 for the Single Rung Ladder).</p>	





Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No	Name and description	Price in NOK
7040	Ladder Single Rung 15m 15m, specifications same as Art No 7039.	
7041	Ladder Single Rung 20m 20m, specifications same as Art No 7039.	
7042	Ladder Double Rung 15m 15m, lightweight, noiseless, non conducting, contains no metal parts and presents no radar signal. Built for heavy duty military use in marine environment! One end of the ladder has a single attachment point for fast and easy deployment. The other end has a two separate attachment points. You can use this side to put 2 ladders together (with the optional TAGS Ladder Connectors) or you can use this side to connect it to two separate anchor points to rig it slightly more stable. Double Rung 390mm width. Rung spacing: 30cm. Using the optional Ladder Connector (Art No 7038) the spacing remains the same when joining two ladders (order 3 for the Double Rung Ladder). The double rung version is faster, more stable and more comfortable to climb than the single rung version. Especially in situations where you must climb downwards.	
7043	Ladder Double Rung 20m 20m, specifications same as Art No 7042.	

Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No	Name and description	Price in NOK
9001	<p>Oil Pen</p> <p>Lubricant, for keeping the launching unit clean and in good working condition. Used once a month. Acid and water free.</p>	
9002	<p>Manometer w/ packing</p> <p>Spare manometer with packing for the Air Cylinder.</p>	
9012	<p>PLT Wall Mount</p> <p>Put your PLT on the wall for safe storage. The height is given by the length of base unit (670 mm) and projectiles (1220mm). The width of each bracket is 600mm.</p> <p>Each module consists of 2 parts (bottom bracket and strapping bracket)</p> <p>Weight: Empty brackets: 5,2 kg. The brackets are made of PE polyethylene plates welded and soft rounded according to regulations.</p>	
9400	<p>Storage Container PLT Rescue 230 complete</p> <p>Water proof container in heavy duty plastic. Easy storage and easy handling. It even floats in the water. Fits PLT Rescue 230 complete. Internal dim. 1350x350x135 mm, External dim. 1410x415x159mm. 63,7liter and 12kg. There are wheels on the container for easy transportation. Color: Black.</p>	

Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No	Name and description	Price in NOK
9401	<p>Storage Container PLT Mini, 75, 125 and 150 complete Water proof container in heavy duty plastic. Easy storage and easy handling. It even floats in the water. Fits PLT Mini, 75, R125 and 150 complete. Internal dim. 939x352x137 mm, External dim. 989x415x157mm. 45liter and 8kg. There are wheels on the container for easy transportation. Color: Black.</p>	
9500	<p>Storage Container Deep Water proof container in heavy Duty plastic. Easy storage and easy handling. It even floats in the water. Internal dim. 1350x350x272 mm, External dim. 1410x415x296mm. 128,5liter and 16kg. There are wheels on the container for easy transportation. Color: Black.</p>	
9900	<p>Bauer Compressor PE100-TE 3 phase 100l/min 225 bar or 330 bar. 200-240V, 400V/440V and 50/60 Hz. Ask for delivery time and price for those specifications. Dimensions is 89x50x49cm and 44kg.</p>	
9901	<p>Bauer Compressor PE100-TW Single phase 100l/min 225 bar or 330 bar. 200-240V, 400V/440V and 50/60 Hz. Ask for delivery time and price for those specifications. Dimensions is 89x50x49cm and app 50kg.</p>	

Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No	Name and description	Price in NOK
9902	<p>Bauer Compressor PE100-TB 4-stroke petrol 100l/min, 4,2 kW, 5,7 Hp. Ask for delivery time and price for those specifications. Dimensions is 89x50x49cm and 42kg.</p>	
9903	<p>Bauer Compressor Junior II, 3 phase Compact Line Junior II 100l/min, 400V 60Hz. 230V is an option. Ask for delivery time and price for those specifications. Dimensions is 66x36x42cm and 46kg.</p>	
BACKPACK KIT	<p>Backpack kit BACKPACK KIT HANDY BACKPACK CARRYING SYSTEM FOR BAGS. All bags are fitted with optional strap for backpack use for Bag 94 and 135.</p>	
BAG 135	<p>Bag 135 L 1300mm W 300mm D 70mm. Fits also in Storage container Art No 9400.</p> <p>Heavy duty padded bags designed in different sizes to suit different models and accessories, to be securely protected and transported. Complete with shoulder straps</p> <ul style="list-style-type: none"> -Heavy duty padded synthetic fabric -Durable zippers with nylon pulls -Neoprene hook&loop side flaps -Adjustable interior straps to secure the PLT position -Exterior padded zipped pouches for accessories <p>All bags are fitted with optional strap for backpack use, ref Art No Backpack kit</p>	

Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No	Name and description	Price in NOK
BAG 94	<p>Bag 94 L 940mm W 300mm D 70mm. Fits also in Storage container Art No 9401.</p> <p>Same product as Bag 135, only smaller.</p>	



Postadresse/mailadress

Restech Norway as
P.O.Box 624
N-8001 Bodø
Norway

Kontoradresse/Officeadress

Restech Norway as
Olav V gt 112
N-8004 Bodø
Norway

Phone: +47 7554 2440
Mail: restech@restech.no
www.restech.no

DNB Bank ASA
Account no: 1503.33.64579
SWIFT: DNBANOKKXXX
IBAN: NO4015033364579